



Catalog Number	Size	Sidewall Code	Diameter (in)	Circ. (in)	Loaded Radius (in)	Load (lbs)	Tread Width (in)	Section Width (in)	Measured Rim	Pressure (psi)	Weight (lbs)	Indicator (in)
Slick												
43410	210/550R13	USF	21.84"	68.61"	10.64"	300	8.68"	10.47"	13" x 10J	20	13.65	0.125"
43475	275/570R13	USF	22.60"	71.00"	11.01"	400	10.80"	12.47"	13" x 12J	20	17.35	0.125"

Vertical Deflection Data

43410 210/550R13		Static Spring Rate (lbf/in)				
Pressure (psi)	Load (lbs)	Camber (deg)				
		0	1	2.25	3	5
24	600	1370	1365	1345	1365	1300
	800	1425	1420	1360	1375	1360
	1000	1525	1530	1415	1410	1385
22	600	1285	1290	1280	1295	1240
	800	1350	1350	1305	1310	1290
	1000	1455	1455	1370	1350	1320
20	600	1185	1190	1185	1210	1165
	800	1260	1265	1225	1225	1205
	1000	1355	1370	1295	1280	1245
18	600	1090	1100	1100	1110	1085
	800	1175	1180	1145	1135	1120
	1000	1270	1280	1225	1210	1165

43475 275/570R13		Static Spring Rate (lbf/in)				
Pressure (psi)	Load (lbs)	Camber (deg)				
		0	1	2.25	3	5
24	600	1825	1795	1725	1635	1465
	800	1810	1790	1795	1715	1590
	1000	1815	1805	1875	1785	1710
22	600	1715	1685	1640	1575	1405
	800	1695	1675	1715	1650	1530
	1000	1715	1700	1795	1730	1655
20	600	1585	1560	1535	1475	1330
	800	1565	1560	1605	1560	1460
	1000	1610	1605	1675	1635	1570
18	600	1450	1430	1425	1380	1250
	800	1425	1435	1485	1465	1270
	1000	1500	1495	1550	1535	1480